

AD-A192 782

A PLANAR IC-COMPATIBLE TRANSFERRED ELECTRON DEVICE FOR  
MILLIMETER-WAVE OPERATION(U) JOHANNES KEPLER UNIV LINZ  
(AUSTRIA) MICROELECTRONICS INST H W THIM 31 AUG 87

1/1


UNCLASSIFIED

DAJA45-86-C-0039

F/G 9/1

NL





MICROCOPY RESOLUTION TEST CHART  
 NBS 1963-A

AD-A192 702

DTIC FILE COPY

②

A planar IC-compatible transferred electron  
device for millimeter-wave operation

Principal Investigator

Prof. Dr. Hartwig Thim, Head of the  
Microelectronics Institute  
University of Linz  
Altenbergerstraße 69  
A-4040 Linz, Austria  
Tel. (0732) 2468 9300

DTIC  
ELECTE  
APR 08 1988  
S D

Contract No. DAJA 45-86-C-0039

"3rd Periodic Report"

March 1st, 1987 - August 31st, 1987

**DISTRIBUTION STATEMENT A**

Approved for public release;  
Distribution Unlimited

The Research reported in this document has  
been made possible through the support and  
sponsorship of the US Government through  
its European Research Office of the US Ar-  
my. ~~This report is intended only for the  
internal management use of the contractor  
and the US Government.~~

88 4 6 10 8

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 3rd report	2. GOVT ACCESSION NO. <b>AD-A192 702</b>	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A planar IC - compatible transferred electron device for millimeter-wave operation		5. TYPE OF REPORT & PERIOD COVERED interim, Mar.87-Aug.87
7. AUTHOR(s)  Hartwig W. Thim		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Microelectronics Institute University of Linz Altenbergerstr. 69, A-4040 Linz, Austria		8. CONTRACT OR GRANT NUMBER(s)  DAJA 45-86-C-0039
11. CONTROLLING OFFICE NAME AND ADDRESS Contracting Office (Mr.G.B.Evans) 47th Area Support Group P.O.Box 160, Warrington,Cheshire,England		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office) USARDS Group UK 223 Old Marylebone Road London NW1 5TH		12. REPORT DATE August 31, 1987
		13. NUMBER OF PAGES six
		15. SECURITY CLASS. (of this report)
16. DISTRIBUTION STATEMENT (of this Report)  This report is intended only for the internal management use of the Contractor and the US Government		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES  2 to 3 times 10 to the 16th power/cc 5 times 10 to the 15th power/cc		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Design rules derived from computer simulations; fabrication of devices with two different gate structures; gain of several db from 26 - 30 GHz; oscillator power of 10mw with 1.2 % efficiency at 29.7 GHz and 1mw with 0.1 % at 37 GHz using dielectric resonators.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Computer simulations have revealed that FEDTEDs operate with high efficiencies of approx. 9 % at lower doping levels ( $5 \cdot 10^{15} \text{ cm}^{-3}$ ) but in a very narrow range of RF/DC voltage levels. Lower efficiencies (3%-6%) are obtainable with doping levels of $(2-3 \cdot 10^{16} \text{ cm}^{-3})$ in a much broader range of RF/DC voltages. Experimental results obtained with a new batch of devices made from epitaxially grown layers with $N_D = 2.5 \cdot 10^{16} \text{ cm}^{-3}$ and $d = 0.9 \mu\text{m}$ are now very encouraging as, for the first time, broad band gain		

20 ABSTRACT continued

of several db from 26 - 30 GHz and, when loaded with a dielectric resonator output power levels of 10mw with 1.2 % efficiency at 29.7 GHz have been obtained. Both, improved device technology and optimized stripline circuitry are made responsible for the improved performance.

Future work will concentrate on pushing efficiencies up by a factor of 5 and on optimizing circuitry for 35 GHz operation.

Keywords: Field Effect Controlled Transferred Electron Devices,

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By <i>per form 50</i>	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
<i>A-1</i>	

SELECTED

The work accomplished during the third period of the contract ending August 31, 1987 includes:

- computer simulation
- device fabrication
- design of stripline circuits
- devices operated as broadband amplifiers (26 - 30 GHz, 37 GHz)
- devices operated as oscillators (10mw, 1.2 %, 30 GHz and 1mw, 0.1 %, 37 GHz)

### Computer simulation

The computer simulations of one-dimensional FETED's have revealed that lower doped devices ( $N_D \approx 5 \cdot 10^{15} \text{ cm}^{-3}$ ) operate with higher efficiencies (~9 %) than higher doped devices ( $N_D \approx 2.5 \cdot 10^{16} \text{ cm}^{-3}$ ) do (~5 %). However, the range of RF and DC drain voltage levels at which the efficiency remains fairly constant (3 - 6 %) is much broader at higher doping levels suggesting that these samples will be tunable over much broader frequency bands than lower doped devices.

Another important conclusion is that maximum efficiencies are attainable at injection current levels of 110 % - 120 % of the valley current defined by  $e \cdot N_D \cdot v_v \cdot A$  ( $e$  = electronic charge,  $N_D$  = doping density,  $v_v = 10^7 \text{ cm/s}$ ,  $A$  = cross sectional area). The injection current level can be adjusted by adjusting the negative gate bias voltage.

The optimum distance between gate and drain is determined by the length of the depletion layer which is for the doping levels used in this simulation around  $3 \mu\text{m}$ . As high fields must be prevented from reaching the drain contact a safe gate to drain distance is 4 -  $5 \mu\text{m}$ . Larger distances add positive series resistance which reduce the efficiency somewhat. Devices with  $10 \mu\text{m}$  long gate to source distance, for example, exhibit efficiencies typically half as large as those  $5 \mu\text{m}$  long devices exhibit.

### Device Fabrication

Device fabrication is now well under control. 95 % of devices made from one chip (which contains typically 60 devices) are mechanically sound. 75 % are electrically (DC-wise) sound. RF-data taken on DC-wise identical devices are

critically dependent on length and placement of bonding wires. More accurate mounting procedures have to be adopted.

### Device Parameters

Due to the one-dimensionality of the computer simulation program the two-dimensional MESFET-like cathode contact structure cannot be simulated and must therefore be optimized empirically. Devices with overlapping ("grounded") gate structure as shown in Fig. 1 exhibit efficiencies only a factor of 2 - 5 smaller than theoretically predicted values. There are experimental indications that connecting the gate to an impedance level other than zero ("grounded gate") might lead to improved performance. Therefore a second type of device structure shown in Fig. 2 has been fabricated and tested. The essential difference to the original structure (Fig. 1) is that the capacitance of the gate with respect to source is significantly smaller than that of the "grounded gate" structure shown in Fig. 1.

### Electrical Characteristics

The low field DC resistance of the devices fabricated during this (third) period of the contract varied between 17 and 60 Ohms in very good agreement with precalculated values. All devices are 400  $\mu\text{m}$  wide.

RF data have been taken in both the stable amplifier mode and in the oscillator mode.

#### a) Broadband amplification

Samples with overlapping gate electrode (Fig. 1) have been operated as stable amplifiers in a circuit configuration as shown in Fig. 3 with the dielectric resonator removed. The FETED is mounted at the end of the 50 Ohm stripline with two radial line stubs connected to gate and source via  $\lambda/2$  line sections providing RF ground potential to both gate and source. Fig. 4 shows both input power  $P_{in}$  and output power  $P_{out}$  versus frequency with several db of gain. 5db of gain compression occurred at this power level and a maximum gain of 10db was obtained when  $P_{in}$  was reduced by a factor of 10. Drain and gate voltages were 6.8V and -4.2V, respectively. The DC drain current was 120mA. Very low gain has been measured around 37 GHz.

b) 30 GHz oscillations

When a 28 GHz dielectric resonator was placed near the drain end of the device oscillations with a maximum output power of 10mw have been observed at 29.7 GHz with 1.2 % DC to RF conversion efficiency. The frequency of oscillation could be changed by 100 MHz with 1db power output reduction by changing the gate bias voltage by a few tenths of a volt.

Devices with finger gate produced only 1mw with 0.1 % efficiency.

c) 37 GHz oscillations

Both types of devices have been operated as oscillators at 37 GHz with only 0.1 % efficiency. Since lower frequency oscillations were absent, the low efficiency can be explained only by poor circuit matching at this frequency.

### Conclusions and Future Research Plan

FECTED's have for the first time produced fundamental frequency oscillations at non-transit-time related frequencies with efficiencies greater than 1 % : 10mw at 30 GHz and several db of reflection gain between 26 and 30 GHz have been obtained. Since computer simulations predict 2 - 5 times higher values over full Ka-band future work during the next contract period (September 87-February 88) will concentrate on further optimizing stripline circuitry including GaAs varactor diodes connected in parallel to the device, minimizing parasitic reactances caused by long bonding wires and reducing the gate length. Gate length reduction down to submicrometer dimensions could possibly increase efficiency as the DC power consumed underneath the gate is lower in a shorter gate region.

### Personnel

Dr. Kurt Lübke, Helmut Scheiber, Thomas Neugebauer, Christoph Schönherr, Gabriele Roitmayr and Johann Katzenmayer.

### Annex

The amount of unused funds remaining on the contract at the end of the period covered by the report is \$ 64,880.00 minus \$ 5,880.00 for which an invoice has been submitted in September, 1987.



Fig.1  
Cross sectional view of  
a FETED with overlapping  
gate




Fig.2  
Cross sectional view of  
a FETED with finger gate




Fig.3  
Microstrip circuit confi-  
guration of a FETED  
oscillator





Fig.4  
Input power  $P_{in}$  and output  
power  $P_{out}$  versus frequency  
of a FETED reflection type  
amplifier



END

DATE

FILMED

6-1988

DTIC